

Models:	elite H 5-25 / elite HC 5-25		
Air-to-water heat pump:	no		
Water-to-water heat pump:	no		
Brine-to-water heat pump:	yes		
Application:	Low temperature (35 °C)		
Equipped with supplementary heater:	no		
Heat pump combination heater:	yes		

Parameter	Symbol	Value	Unit	Parameter	Symbol	Value	Unit																																																																																				
Rated heat output	Prated	25	kW	Energy efficiency	$\eta_s$	219	%																																																																																				
Declared heating capacity for part load at inner temperature of 20 °C and outdoor temperature $T_j$				Declared COP for part load at inner temperature of 20 °C and outdoor temperature $T_j$																																																																																							
$T_j = - 7 \text{ } ^\circ\text{C}$	Pdh	22.2	kW	$T_j = - 7 \text{ } ^\circ\text{C}$	COPd	4.7	-																																																																																				
$T_j = + 2 \text{ } ^\circ\text{C}$	Pdh	13.5	kW	$T_j = + 2 \text{ } ^\circ\text{C}$	COPd	5.5	-																																																																																				
$T_j = + 7 \text{ } ^\circ\text{C}$	Pdh	8.7	kW	$T_j = + 7 \text{ } ^\circ\text{C}$	COPd	5.9	-																																																																																				
$T_j = + 12 \text{ } ^\circ\text{C}$	Pdh	5	kW	$T_j = + 12 \text{ } ^\circ\text{C}$	COPd	6.3	-																																																																																				
$T_j$ = bivalent temperature	Pdh	-	kW	$T_j$ = bivalent temperature	COPd	-	-																																																																																				
$T_j$ = limit temperature	Pdh	-	kW	$T_j$ = limit temperature	COPd	-	-																																																																																				
Air-to-water heat pumps: $T_j = - 15 \text{ } ^\circ\text{C}$ (if $TOL < - 20 \text{ } ^\circ\text{C}$ )	Pdh		kW	Air-to-water heat pumps: $T_j = - 15 \text{ } ^\circ\text{C}$ (if $TOL < - 20 \text{ } ^\circ\text{C}$ )	COPd	-	%																																																																																				
Bivalent temperature	$T_{biv}$	-	°C	In air-to-water heat pumps: limit temperature	TOL	-	°C																																																																																				
Cycling interval capacity for heating	Pcyc	-	kW	Cycling interval COP	COPcyc	-	%																																																																																				
Degradation coefficient	Cdh	0.9	-	Heating water operating limit	WTOL	65	°C																																																																																				
Power consumption in modes different than active mode																																																																																											
Off mode	P <sub>OFF</sub>	0.005	kW	Supplementary heater																																																																																							
Off by thermostat	P <sub>TO</sub>	0.010	kW	Standby mode	P <sub>SB</sub>	0.010	kW	Rated heat output	P <sub>TO</sub>	-	kW	Crankcase heater mode	P <sub>CK</sub>	0.000	kW	Type of energy input								Other parameters								Capacity control	variable			Air-to-water heat pumps: Nominal airflow	-	-	m <sup>3</sup> /h	Sound power level (indoor/outdoor)	L <sub>WA</sub>	42 / 0	dB	Water-to-water and brine-to-water heat pumps: Nominal flow rates of water or brine in outdoor heat exchanger	-	4.02	m <sup>3</sup> /h	Annual energy consumption:	Q <sub>HE</sub>	9666	kWh	For heat pump combination heater:								Declared load profile	XL			For heat pump combination heater:				Daily electricity consumption	Q <sub>elec</sub>	9.32	kWh	Water heating energy efficiency	$\eta_{wh}$	107	%	Annual energy consumption	AEC	2066	kWh	Daily fuel consumption	Q <sub>fuel</sub>	-	kWh					Annual fuel consumption	AFC	-	GJ
Standby mode	P <sub>SB</sub>	0.010	kW	Rated heat output	P <sub>TO</sub>	-	kW																																																																																				
Crankcase heater mode	P <sub>CK</sub>	0.000	kW	Type of energy input								Other parameters								Capacity control	variable			Air-to-water heat pumps: Nominal airflow	-	-	m <sup>3</sup> /h	Sound power level (indoor/outdoor)	L <sub>WA</sub>	42 / 0	dB	Water-to-water and brine-to-water heat pumps: Nominal flow rates of water or brine in outdoor heat exchanger	-	4.02	m <sup>3</sup> /h	Annual energy consumption:	Q <sub>HE</sub>	9666	kWh	For heat pump combination heater:								Declared load profile	XL			For heat pump combination heater:				Daily electricity consumption	Q <sub>elec</sub>	9.32	kWh	Water heating energy efficiency	$\eta_{wh}$	107	%	Annual energy consumption	AEC	2066	kWh	Daily fuel consumption	Q <sub>fuel</sub>	-	kWh					Annual fuel consumption	AFC	-	GJ												
Type of energy input																																																																																											
Other parameters																																																																																											
Capacity control	variable			Air-to-water heat pumps: Nominal airflow	-	-	m <sup>3</sup> /h																																																																																				
Sound power level (indoor/outdoor)	L <sub>WA</sub>	42 / 0	dB	Water-to-water and brine-to-water heat pumps: Nominal flow rates of water or brine in outdoor heat exchanger	-	4.02	m <sup>3</sup> /h																																																																																				
Annual energy consumption:	Q <sub>HE</sub>	9666	kWh	For heat pump combination heater:								Declared load profile	XL			For heat pump combination heater:				Daily electricity consumption	Q <sub>elec</sub>	9.32	kWh	Water heating energy efficiency	$\eta_{wh}$	107	%	Annual energy consumption	AEC	2066	kWh	Daily fuel consumption	Q <sub>fuel</sub>	-	kWh					Annual fuel consumption	AFC	-	GJ																																																
For heat pump combination heater:																																																																																											
Declared load profile	XL			For heat pump combination heater:																																																																																							
Daily electricity consumption	Q <sub>elec</sub>	9.32	kWh	Water heating energy efficiency	$\eta_{wh}$	107	%																																																																																				
Annual energy consumption	AEC	2066	kWh	Daily fuel consumption	Q <sub>fuel</sub>	-	kWh																																																																																				
				Annual fuel consumption	AFC	-	GJ																																																																																				

Contact information CLAUSIUS SYSTEMS S.L. (CEO2 GREEN S.L.)	Polígono Industrial P.P.Sur–PPI 5 Naves 8 y 9 36475, O Porriño (Pontevedra) SPAIN	Edificio Fundición Campus Universitario de Vigo 36310 Vigo (Pontevedra) SPAIN	+34 886 11 36 11 <a href="mailto:info@clausius.es">info@clausius.es</a> <a href="http://www.clausius.es">www.clausius.es</a>
---	---	--	--